



Control Damper Features

- 15" w.g. Maximum Standard Static Pressure (Higher Pressure Models are Available)
- Special Configurations are Available
- Manual, Pneumatic or Electric Actuators are Available
- Pneumatic and Electronic Positioners are Available
- Complete Environmental Qualifications (Including Seismic)
- Available with Solenoid Valves or Limit Switches
- Stainless Steel or Silicone Blade Seals (Other Types are Available)
- Low Pressure Drop
- ANSI Class II or Class III Leakage Rate as Applicable
- Welding and Inspections in Accordance with AWS and/or ASME as Required
- Manufactured In Accordance With Our Quality Assurance Program







Control Damper Features

- 15" w.g. Maximum Standard Static Pressure (Higher Pressure Models are Available)
- Special Configurations are Available
- Manual Locking Quadrants, Handwheel or Pull-Chain Actuators are Available
- Complete Environmental Qualifications (Including Seismic)
- Available with Limit Switches
- Stainless Steel or Silicone Blade Seals for Leakage Class II / III (Other Types are Available)
- Low Pressure Drop
- ANSI Class II, Class III or Class IV Leakage Rate as Applicable
- Welding and Inspections in Accordance with AWS and/or ASME as Required
- Manufactured In Accordance With Our Quality Assurance Program